



## Outdoor refreshment

The Outdoor, IP34-certified anti-rain version of SandenVendo's popular G-Drink model combines all the utmost innovations of a premium automatic vending machine with the newly-developed features required for outdoor usage, including an anti-condensation heated glass, a roof, and an anti-vandal front door for further protection. Thanks to its thermal-magnetic circuit breaker and its anti-freezing function with temperature control specially designed for outdoor applications, G-Drink Outdoor can also operate under below-zero temperature conditions, while its LED illumination system serves as an impulse sales ally during shop-closing hours.

DM9 OD

# G-Drink Standard 9 Vertical Outdoor

## TECHNICAL SPECIFICATIONS

## DM9 OD

|                                                 |                       |
|-------------------------------------------------|-----------------------|
| DIMENSIONS H x W x D (mm)                       | 1875* x 1260 x 1010   |
| WEIGHT (NET - Standard machine without options) | 410 Kg                |
| NO. OF SELECTIONS PER SHELF                     | 9                     |
| NO. OF SHELVES                                  | Standard 5 / Max. 7   |
| NO. OF SELECTIONS                               | Standard 45 / Max. 63 |
| MAX. CAPACITY (0.33 l CANS)                     | 504                   |
| MAX. CAPACITY (0.50 l PET BOTTLES)              | 360                   |
| PROTOCOL                                        | Executive / MDB       |
| COOLING SYSTEM CONTROL                          | Electronic            |
| INTERNAL TEMPERATURE RANGE                      | +2°C up to +10°C      |
| AMBIENT TEMPERATURE RANGE                       | -15°C up to +38°C     |
| COOLING UNIT                                    | HCD                   |
| POWER SUPPLY                                    | 230/240 V - 50/60 Hz  |
| MAX. POWER CONSUMPTION                          | 490 W                 |
| ENERGY CLASS                                    | E                     |
| ENERGY CONSUMPTION - kWh/annum                  | 1700                  |

\*With adjustable leveling screw

## OPTIONAL

SPECIAL CODED LOCK (RIELDA)  
 LOCK PROTECTION  
 SECURITY CASH BOX SYSTEM  
 WALL/FLOOR FIXING KIT  
 PAYMENT SYSTEM  
 KIT EVA DTS  
 VARIOUS FITTING KITS  
 CUSTOMIZATION  
 CUSTOMIZED CABINET COLOUR



## Outdoor refreshment

The Outdoor, IP34-certified anti-rain version of SandenVendo's popular G-Drink model combines all the utmost innovations of a premium automatic vending machine with the newly-developed features required for outdoor usage, including an anti-condensation heated glass, a roof, and an anti-vandal front door for further protection. Thanks to its thermal-magnetic circuit breaker and its anti-freezing function with temperature control specially designed for outdoor applications, G-Drink Outdoor can also operate under below-zero temperature conditions, while its LED illumination system serves as an impulse sales ally during shop-closing hours.

DM6 OD

# G-Drink Standard 6 Vertical Outdoor

## TECHNICAL SPECIFICATIONS

## DM6 OD

|                                                 |                       |
|-------------------------------------------------|-----------------------|
| DIMENSIONS H x W x D (mm)                       | 1875*x 990 x 1010     |
| WEIGHT (NET - Standard machine without options) | 350 Kg                |
| NO. OF SELECTIONS PER SHELF                     | 6                     |
| NO. OF SHELVES                                  | Standard 5 / Max. 7   |
| NO. OF SELECTIONS                               | Standard 30 / Max. 42 |
| MAX. CAPACITY (0.33 l CANS)                     | 336                   |
| MAX. CAPACITY (0.50 l PET BOTTLES)              | 240                   |
| PROTOCOL                                        | Executive / MDB       |
| COOLING SYSTEM CONTROL                          | Electronic            |
| INTERNAL TEMPERATURE RANGE                      | +2°C up to +10°C      |
| AMBIENT TEMPERATURE RANGE                       | -15°C up to +38°C     |
| COOLING UNIT                                    | HCD                   |
| POWER SUPPLY                                    | 230/240 V - 50/60 Hz  |
| MAX. POWER CONSUMPTION                          | 490 W                 |
| ENERGY CLASS                                    | E                     |
| ENERGY CONSUMPTION - kWh/annum                  | 1290                  |

\*With adjustable leveling screw

## OPTIONAL

SPECIAL CODED LOCK (RIELDA)  
 LOCK PROTECTION  
 SECURITY CASH BOX SYSTEM  
 WALL/FLOOR FIXING KIT  
 PAYMENT SYSTEM  
 KIT EVA DTS  
 VARIOUS FITTING KITS  
 CUSTOMIZATION  
 CUSTOMIZED CABINET COLOUR