



Hydro-lution

The most successful glass-front vending machine of our history renovates its look in a modern, sophisticated yet timeless way. Conceived with a new, brighter LED illumination structure to enhance the visibility of the drinks displayed inside, G-Drink Design is equipped with an innovative, back-lit keypad to ease the selection operations in both luminous and dark venues.

Available in two models, with 9 or 6 selections per shelf, G-Drink Design is geared up with a vertical lift system and all of SandenVendo's top-notch cooling technologies and an easy door-latching system.

DV9

G-Drink Design 9 Vertical

TECHNICAL SPECIFICATIONS

	DV9
DIMENSIONS H x W x D (mm)	1830* x 1215 x 845
WEIGHT (NET - Standard machine without options)	345 Kg
NO. OF SELECTIONS PER SHELF	9
NO. OF SHELVES	Standard 5 / Max. 7
NO. OF SELECTIONS	Standard 45 / Max. 63
MAX. CAPACITY (0.33 l CANS)	504
MAX. CAPACITY (0.50 l PET BOTTLES)	360
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
MAX. POWER CONSUMPTION	450 W
POWER SUPPLY	230/240 V - 50/60 Hz
ENERGY CLASS	D
ENERGY CONSUMPTION - kWh/annum	1562

* With adjustable leveling screw

OPTIONAL

- CUSTOMIZED CABINET COLOUR
- SPECIAL CODED LOCK (RIELDA)
- ANTI-VANDALISM KEY PAD AND SAFETY COIN INSERT
- WALL/FLOOR FIXING KIT
- LOCK PROTECTION
- FRONT GLASS PROTECTION
- PRODUCT SPACERS
- VARIOUS FITTING KITS
- BRANDING
- SECURITY CASH BOX SYSTEM
- CO2 COOLING UNIT AVAILABLE



Hydro-lution

The most successful glass-front vending machine of our history renovates its look in a modern, sophisticated yet timeless way. Conceived with a new, brighter LED illumination structure to enhance the visibility of the drinks displayed inside, G-Drink Design is equipped with an innovative, back-lit keypad to ease the selection operations in both luminous and dark venues.

Available in two models, with 9 or 6 selections per shelf, G-Drink Design is geared up with a vertical lift system and all of SandenVendo's top-notch cooling technologies and an easy door-latching system.

DC6

G-Drink Design 6 Vertical

TECHNICAL SPECIFICATIONS

	DC6
DIMENSIONS H x W x D (mm)	1830* x 940 x 845
WEIGHT (NET - Standard machine without options)	295 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 5 / Max. 7
NO. OF SELECTIONS	Standard 30 / Max. 42
MAX. CAPACITY (0.33 l CANS)	336
MAX. CAPACITY (0.50 l PET BOTTLES)	240
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
MAX. POWER CONSUMPTION	450 W
POWER SUPPLY	230/240 V - 50/60 Hz
ENERGY CLASS	D
ENERGY CONSUMPTION - kWh/annum	1330

* With adjustable leveling screw

OPTIONAL

- CUSTOMIZED CABINET COLOUR
- SPECIAL CODED LOCK (RIELDA)
- ANTI-VANDALISM KEY PAD AND SAFETY COIN INSERT
- WALL/FLOOR FIXING KIT
- LOCK PROTECTION
- FRONT GLASS PROTECTION
- PRODUCT SPACERS
- VARIOUS FITTING KITS
- BRANDING
- SECURITY CASH BOX SYSTEM
- CO2 COOLING UNIT AVAILABLE