





Better together

G-Snack Standard Slave is the automatic vending machine that benefits from all the perks of the leading vending machine models on the market but on a budget. Backed with SandenVendo's expertise in thermo-dynamics and cooling systems, G-Snack Standard Slave will broaden your vending possibilities by simply pairing with any G Caffè, G-Drink or G-Snack master model available. Versatile by nature, this automatic slave vending machine can accommodate up to 10, 8 or 6 selections per shelf among snacks, drinks, lunch bites and dairy products thanks to its temperature range that goes from +2°C to +18°C. Its extreme versatility allows G-Snack Standard Slave to be suitable for installation inside automated shops as an... (more at our website)

SSX-B / KSX-B

G-Snack Standard Ten (X) Slave

Cat. 4)
(

^{*}With adjustable feet

OPTIONAL

SPEEDY LIFT
E-LABELING
ROTARY SYSTEM
BELT SYSTEM
KIT SANDWICH
KIT BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
WALL/FLOOR FIXING KIT
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED CABINET COLOUR







Better together

G-Snack Standard Slave is the automatic vending machine that benefits from all the perks of the leading vending machine models on the market but on a budget. Backed with SandenVendo's expertise in thermo-dynamics and cooling systems, G-Snack Standard Slave will broaden your vending possibilities by simply pairing with any G Caffè, G-Drink or G-Snack master model available. Versatile by nature, this automatic slave vending machine can accommodate up to 10, 8 or 6 selections per shelf among snacks, drinks, lunch bites and dairy products thanks to its temperature range that goes from +2°C to +18°C. Its extreme versatility allows G-Snack Standard Slave to be suitable for installation inside automated shops as an... (more at our website)

SS8-B/KS8-B

G-Snack Standard Eight (VIII) Slave

TECHNICAL SPECIFICATIONS	SS8-B / KS8-B
DIMENSIONS H x W x D (mm)	1830 x 830 x 845
WEIGHT (NET - Standard machine without options)	240 kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 56
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
CLIMATE CLASS	ST (+16°C up to +38°C)
COOLING UNIT	HCD
POWER SUPPLY	230 V / 50 Hz
MAX. POWER CONSUMPTION	350 W
ENERGY CLASS	C (Cat. 2) C (Cat. 3) C (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	681 (Cat. 2) 849 (Cat. 3) 878 (Cat. 4)

^{*}With adjustable feet

OPTIONAL

SPEEDY LIFT
E-LABELING
ROTARY SYSTEM
BELT SYSTEM
KIT SANDWICH
KIT BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
WALL/FLOOR FIXING KIT
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED CABINET COLOUR







Better together

G-Snack Standard Slave is the automatic vending machine that benefits from all the perks of the leading vending machine models on the market but on a budget. Backed with SandenVendo's expertise in thermo-dynamics and cooling systems, G-Snack Standard Slave will broaden your vending possibilities by simply pairing with any G Caffè, G-Drink or G-Snack master model available. Versatile by nature, this automatic slave vending machine can accommodate up to 10, 8 or 6 selections per shelf among snacks, drinks, lunch bites and dairy products thanks to its temperature range that goes from +2°C to +18°C. Its extreme versatility allows G-Snack Standard Slave to be suitable for installation inside automated shops as an... (more at our website)

SS6-B/KS6-B

G-Snack Standard Six (VI) Slave

TECHNICAL SPECIFICATIONS	SS6-B / KS6-B
DIMENSIONS H x W x D (mm)	1830*x 685 x 845
WEIGHT (NET - Standard machine without options)	220 kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 42
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
CLIMATE CLASS	ST (+16 °C up to +38 °C)
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	350 W
ENERGY CLASS	C (Cat. 2) C (Cat. 3) C (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	629 (Cat. 2) 798 (Cat. 3) 793 (Cat. 4)

^{*}With adjustable feet

OPTIONAL

SPEEDY LIFT
E-LABELING
ROTARY SYSTEM
BELT SYSTEM
KIT SANDWICH
KIT BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
WALL/FLOOR FIXING KIT
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED CABINET COLOUR