



Proper snacking attitude

Backed by SandenVendo's expertise in thermo-dynamics and cooling technologies, G-Snack Standard is the automatic vending machine equipped with the same software and technology features of the Design line, at a budget.

Spacious and versatile as every G-Snack model, the new G-Snack Standard XII model can accommodate up to 84 selections including a vast assortment of bulk-size and Extra-Vending merchandises thanks to an extremely flexible tray configuration system and a new speedy elevator, turning this automatic vending machine into a mini-market open 24/7.

SML

G-Snack Standard Twelve (XII) Master - SML

TECHNICAL SPECIFICATIONS	SML
DIMENSIONS H x W x D (mm)	1830* x 1290 x 900
WEIGHT (NET - Standard machine without options)	410 Kg
NO. OF SELECTIONS PER SHELF	12 (6 + 6)
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 84
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	460 W
POWER SUPPLY	230/240 V - 50/60 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	D (Cat. 2) D (Cat. 3) D (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1288 (Cat. 2) 1762 (Cat. 3) 1674 (Cat. 4)

* With adjustable feet



Proper snacking attitude

Backed by SandenVendo's expertise in thermo-dynamics and cooling technologies, G-Snack Standard is the automatic vending machine equipped with the same software and technology features of the Design line, at a budget.

Spacious and versatile as every G-Snack model, the new G-Snack Standard XII model can accommodate up to 84 selections including a vast assortment of bulk-size and Extra-Vending merchandises thanks to an extremely flexible tray configuration system and a new speedy elevator, turning this automatic vending machine into a mini-market open 24/7.

SMX

G-Snack Standard Ten (X) Master - SMX

TECHNICAL SPECIFICATIONS

	SMX
DIMENSIONS H x W x D (mm)	1830* x 1125 x 845
WEIGHT (NET - Standard machine without options)	340 Kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 70
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	460 W
POWER SUPPLY	230/240 V - 50/60 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	D (Cat. 2) D (Cat. 3) D (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1087 (Cat. 2) 1666 (Cat. 3) 1607 (Cat. 4)

* With adjustable feet

OPTIONAL

SPEEDY LIFT
DUO SYNCHRO SPIRAL (NEW)
DOUBLE SPIRAL MOTOR
DUO DIVIDER
KIT SANDWICH / BAGUETTE
7TH SHELF
FRONT GLASS PROTECTION
LOCK PROTECTION
WALL/FLOOR FIXING KIT
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
BRANDING
CUSTOMIZED CABINET COLOUR
CO2 COOLING UNIT AVAILABLE



Proper snacking attitude

Backed by SandenVendo's expertise in thermo-dynamics and cooling technologies, G-Snack Standard is the automatic vending machine equipped with the same software and technology features of the Design line, at a budget.

Spacious and versatile as every G-Snack model, the new G-Snack Standard XII model can accommodate up to 84 selections including a vast assortment of bulk-size and Extra-Vending merchandises thanks to an extremely flexible tray configuration system and a new speedy elevator, turning this automatic vending machine into a mini-market open 24/7.

SM8

G-Snack Standard Eight (VIII) Master - SM8

TECHNICAL SPECIFICATIONS

SM8

DIMENSIONS H x W x D (mm)	1830* x 980 x 845
WEIGHT (NET - Standard machine without options)	310 Kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 56
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	460 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	D (Cat. 2) D (Cat. 3) D (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	975 (Cat. 2) 1569 (Cat. 3) 1521 (Cat. 4)

* With adjustable leveling screw

OPTIONAL

SPEEDY LIFT
DUO SYNCHRO SPIRAL (NEW)
DOUBLE SPIRAL MOTOR
DUO DIVIDER
KIT SANDWICH / BAGUETTE
7TH SHELF
FRONT GLASS PROTECTION
LOCK PROTECTION
WALL/FLOOR FIXING KIT
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
BRANDING
CUSTOMIZED CABINET COLOUR
CO2 COOLING UNIT AVAILABLE



Proper snacking attitude

Backed by SandenVendo's expertise in thermo-dynamics and cooling technologies, G-Snack Standard is the automatic vending machine equipped with the same software and technology features of the Design line, at a budget.

Spacious and versatile as every G-Snack model, the new G-Snack Standard XII model can accommodate up to 84 selections including a vast assortment of bulk-size and Extra-Vending merchandises thanks to an extremely flexible tray configuration system and a new speedy elevator, turning this automatic vending machine into a mini-market open 24/7.

SM6

G-Snack Standard Six (VI) Master - SM6

TECHNICAL SPECIFICATIONS

SM6

DIMENSIONS H x W x D (mm)	1830* x 830 x 845
WEIGHT (NET - Standard machine without options)	275 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 42
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	500 W
POWER SUPPLY	230/240 V - 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1231 (Cat. 2) 1703 (Cat. 3) 1703 (Cat. 4)

* With adjustable feet

OPTIONAL

SPEEDY LIFT
DUO SYNCHRO SPIRAL (NEW)
DOUBLE SPIRAL MOTOR
DUO DIVIDER
KIT SANDWICH / BAGUETTE
7TH SHELF
FRONT GLASS PROTECTION
LOCK PROTECTION
WALL/FLOOR FIXING KIT
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
BRANDING
CUSTOMIZED CABINET COLOUR
CO2 COOLING UNIT AVAILABLE