



Better together

G-Snack Standard Slave is the automatic vending machine that benefits from all the perks of the leading vending machine models on the market but on a budget. Backed with SandenVendo's expertise in thermo-dynamics and cooling systems, G-Snack Standard Slave will broaden your vending possibilities by simply pairing with any G Caffè, G-Drink or G-Snack master model available. Versatile by nature, this automatic slave vending machine can accommodate up to 10, 8 or 6 selections per shelf among snacks, drinks, lunch bites and dairy products thanks to its temperature range that goes from +2°C to +18°C. Its extreme versatility allows G-Snack Standard Slave to be suitable for installation inside automated shops as an... [\(more at our website\)](#)

SSX-B / KSX-B

G-Snack Standard Ten (X) Slave

TECHNICAL SPECIFICATIONS

	SSX-B / KSX-B
DIMENSIONS H x W x D (mm)	1830 x 980 x 845
WEIGHT (NET - Standard machine without options)	290 kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 70
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	460 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	D (Cat. 2) D (Cat. 3) D (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1087 (Cat. 2) 1666 (Cat. 3) 1607 (Cat. 4)

* With adjustable feet

OPTIONAL

- SPEEDY LIFT
- DUO SYNCHRO SPIRAL (NEW)
- DOUBLE SPIRAL MOTOR
- DUO DIVIDER
- KIT SANDWICH / BAGUETTE
- 7TH SHELF
- WALL/FLOOR FIXING KIT
- SPECIAL CODED LOCK (RIELDA)
- SECURITY CASH BOX SYSTEM
- BRANDING
- CUSTOMIZED CABINET COLOUR



Better together

G-Snack Standard Slave is the automatic vending machine that benefits from all the perks of the leading vending machine models on the market but on a budget. Backed with SandenVendo's expertise in thermo-dynamics and cooling systems, G-Snack Standard Slave will broaden your vending possibilities by simply pairing with any G Caffè, G-Drink or G-Snack master model available. Versatile by nature, this automatic slave vending machine can accommodate up to 10, 8 or 6 selections per shelf among snacks, drinks, lunch bites and dairy products thanks to its temperature range that goes from +2°C to +18°C. Its extreme versatility allows G-Snack Standard Slave to be suitable for installation inside automated shops as an... [\(more at our website\)](#)

SS8-B / KS8-B

G-Snack Standard Eight (VIII) Slave

TECHNICAL SPECIFICATIONS

SS8-B / KS8-B

DIMENSIONS H x W x D (mm)	1830 x 830 x 845
WEIGHT (NET - Standard machine without options)	240 kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 56
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	460 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	D (Cat. 2) D (Cat. 3) D (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	975 (Cat. 2) 1569 (Cat. 3) 1521 (Cat. 4)

*With adjustable feet

OPTIONAL

SPEEDY LIFT
DUO SYNCHRO SPIRAL (NEW)
DOUBLE SPIRAL MOTOR
DUO DIVIDER
KIT SANDWICH / BAGUETTE
7TH SHELF
WALL/FLOOR FIXING KIT
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
BRANDING
CUSTOMIZED CABINET COLOUR



Better together

G-Snack Standard Slave is the automatic vending machine that benefits from all the perks of the leading vending machine models on the market but on a budget. Backed with SandenVendo's expertise in thermo-dynamics and cooling systems, G-Snack Standard Slave will broaden your vending possibilities by simply pairing with any G Caffè, G-Drink or G-Snack master model available. Versatile by nature, this automatic slave vending machine can accommodate up to 10, 8 or 6 selections per shelf among snacks, drinks, lunch bites and dairy products thanks to its temperature range that goes from +2°C to +18°C. Its extreme versatility allows G-Snack Standard Slave to be suitable for installation inside automated shops as an... [\(more at our website\)](#)

SS6-B / KS6-B

G-Snack Standard Six (VI) Slave

TECHNICAL SPECIFICATIONS

SS6-B / KS6-B

DIMENSIONS H x W x D (mm)	1830* x 685 x 845
WEIGHT (NET - Standard machine without options)	220 kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 42
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	500 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16 °C up to +38 °C)
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1231 (Cat. 2) 1703 (Cat. 3) 1703 (Cat. 4)

* With adjustable feet

OPTIONAL

- SPEEDY LIFT
- DUO SYNCHRO SPIRAL (NEW)
- DOUBLE SPIRAL MOTOR
- DUO DIVIDER
- KIT SANDWICH / BAGUETTE
- 7TH SHELF
- WALL/FLOOR FIXING KIT
- SPECIAL CODED LOCK (RIELDA)
- SECURITY CASH BOX SYSTEM
- BRANDING
- CUSTOMIZED CABINET COLOUR