





Essentials at your fingertips

Versatile and smart, G-Snack Touch is the automatic vending machine designed to increase your profits in the most effortless and intuitive way possible by combining top-notch technology with SandenVendo's flagship cooling units.

G-Snack Touch, equipped with a user-friendly and commercially advantaging touch display with a multi-selection feature to persuade clients into buying more products, can accommodate a large variety of cold drinks, snacks and foods including fresh goods such as lunch boxes or salads on the go; its extreme flexibility allows G-Snack Touch to be suitable for installation inside automated shops as an Extra-Vending machine that dispenses merchandising items.

STX

G-Snack Touch Ten (X) Master

TECHNICAL SPECIFICATIONS	STX
DIMENSIONS H x W x D (mm)	1830* x 1125 x 845
WEIGHT (NET - Standard machine without options)	340 Kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 70
DISPLAY	7" Touch screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	460 W
POWER SUPPLY	230/240 V - 50/60 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	D (Cat. 2) D (Cat. 3) D (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1087 (Cat. 2) 1666 (Cat. 3) 1607 (Cat. 4)

* With adjustable feet

 ${\small @ SandenVendo \,GmbH} \\$

Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.







Essentials at your fingertips

Versatile and smart, G-Snack Touch is the automatic vending machine designed to increase your profits in the most effortless and intuitive way possible by combining top-notch technology with SandenVendo's flagship cooling units.

G-Snack Touch, equipped with a user-friendly and commercially advantaging touch display with a multi-selection feature to persuade clients into buying more products, can accommodate a large variety of cold drinks, snacks and foods including fresh goods such as lunch boxes or salads on the go; its extreme flexibility allows G-Snack Touch to be suitable for installation inside automated shops as an Extra-Vending machine that dispenses merchandising items.

ST8

G-Snack Touch Eight (VIII) Master

TECHNICAL SPECIFICATIONS	ST8
DIMENSIONS H x W x D (mm)	1830* x 980 x 845
WEIGHT (NET - Standard machine without options)	310 Kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 56
DISPLAY	7" Touch screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	460 W
POWER SUPPLY	230/240 V - 50/60 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	D (Cat. 2) D (Cat. 3) D (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	975 (Cat. 2) 1569 (Cat. 3) 1521 (Cat. 4)

 * With adjustable leveling screw

© SandenVendo GmbH

Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.







Essentials at your fingertips

Versatile and smart, G-Snack Touch is the automatic vending machine designed to increase your profits in the most effortless and intuitive way possible by combining top-notch technology with SandenVendo's flagship cooling units.

G-Snack Touch, equipped with a user-friendly and commercially advantaging touch display with a multi-selection feature to persuade clients into buying more products, can accommodate a large variety of cold drinks, snacks and foods including fresh goods such as lunch boxes or salads on the go; its extreme flexibility allows G-Snack Touch to be suitable for installation inside automated shops as an Extra-Vending machine that dispenses merchandising items.

ST6

G-Snack Touch Six (VI) Master

TECHNICAL SPECIFICATIONS	ST6
DIMENSIONS H x W x D (mm)	1830* x 830 x 845
WEIGHT (NET - Standard machine without options)	275 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 42
DISPLAY	7" Touch screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	НС
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	500 W
POWER SUPPLY	230/240 V - 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1231 (Cat. 2) 1703 (Cat. 3) 1703 (Cat. 4)

* With adjustable feet

 ${\small @ SandenVendo \,GmbH} \\$

Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.