



## Designed for workers, joggers and wanderers

Once again, the most versatile vending machine of all times has just outdid itself. Now available with top-notch touch screen display designed for quick and multi-purchasing operations, G-Snack Touch Outdoor represents a safe, smart and innovative choice for satisfying large array of customers needs. From drinks and edibles of all sorts, including freshly harvested products for a healthy lunch in the park or a last-minute family picnic, G-Snack Touch Outdoor can accommodate a broad variety of products including Extra Vending items such as protection materials, hi-tech devices or pet food: you decide!

STX OD

# G-Snack Ten (X) Touch Outdoor

## TECHNICAL SPECIFICATIONS

	STX OD
DIMENSIONS H x W x D (mm)	1900 x 1200 x 1010
WEIGHT (NET - Standard machine without options)	400 kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / max. 7
NO. OF SELECTIONS	max. 70
DISPLAY	7" Touch Screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +38°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	450 W
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1553 (Cat. 2) 1836 (Cat. 3) 1714 (Cat. 4)

## OPTIONAL

- SPEEDY LIFT
- E-LABELING
- ROTARY SYSTEM
- BELT SYSTEM
- KIT SANDWICH
- KIT BAGUETTE
- MOTORIZED LOCK DELIVERY EYELET
- SPECIAL CODED LOCK (RIELDA)
- SECURITY CASH BOX SYSTEM
- WALL/FLOOR FIXING KIT
- PAYMENT SYSTEM
- KIT EVA DTS
- VARIOUS FITTING KITS



## Designed for workers, joggers and wanderers

Once again, the most versatile vending machine of all times has just outdid itself. Now available with top-notch touch screen display designed for quick and multi-purchasing operations, G-Snack Touch Outdoor represents a safe, smart and innovative choice for satisfying large array of customers needs. From drinks and edibles of all sorts, including freshly harvested products for a healthy lunch in the park or a last-minute family picnic, G-Snack Touch Outdoor can accommodate a broad variety of products including Extra Vending items such as protection materials, hi-tech devices or pet food: you decide!

ST8 OD

# G-Snack Eight (VIII) Touch Outdoor

## TECHNICAL SPECIFICATIONS

## ST8 OD

DIMENSIONS H x W x D (mm)	1900 x 1030 x 1010
WEIGHT (NET - Standard machine without options)	350 Kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / max. 7
NO. OF SELECTIONS	max. 56
DISPLAY	7" Touch Screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +38°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	450 W
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1232 (Cat. 2) 1619 (Cat. 3) 1414 (Cat. 4)

## OPTIONAL

- SPEEDY LIFT
- E-LABELING
- BELT SYSTEM
- ROTARY SYSTEM
- KIT SANDWICH
- KIT BAGUETTE
- MOTORIZED LOCK DELIVERY EYELET
- SPECIAL CODED LOCK (RIELDA)
- SECURITY CASH BOX SYSTEM
- WALL/FLOOR FIXING KIT
- PAYMENT SYSTEM
- KIT EVA DTS
- VARIOUS FITTING KITS



## Designed for workers, joggers and wanderers

Once again, the most versatile vending machine of all times has just outdid itself. Now available with top-notch touch screen display designed for quick and multi-purchasing operations, G-Snack Touch Outdoor represents a safe, smart and innovative choice for satisfying large array of customers needs. From drinks and edibles of all sorts, including freshly harvested products for a healthy lunch in the park or a last-minute family picnic, G-Snack Touch Outdoor can accommodate a broad variety of products including Extra Vending items such as protection materials, hi-tech devices or pet food: you decide!

ST6 OD

# G-Snack Six (VI) Touch Outdoor

## TECHNICAL SPECIFICATIONS

	ST6 OD
DIMENSIONS H x W x D (mm)	1900 x 890 x 1010
WEIGHT (NET - Standard machine without options)	325 kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / max. 7
NO. OF SELECTIONS	max. 42
DISPLAY	7" Touch Screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +38°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	450 W
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1280 (Cat. 2) 1518 (Cat. 3) 1545 (Cat. 4)

## OPTIONAL

- SPEEDY LIFT
- E-LABELING
- ROTARY SYSTEM
- BELT SYSTEM
- KIT SANDWICH
- KIT BAGUETTE
- MOTORIZED LOCK DELIVERY EYELET
- SPECIAL CODED LOCK (RIELDA)
- SECURITY CASH BOX SYSTEM
- WALL/FLOOR FIXING KIT
- PAYMENT SYSTEM
- KIT EVA DTS
- VARIOUS FITTING KITS