





DO IT SMART, BACK-LOAD IT

Load the vending machine directly from your shop.

The smart, easy and eco-friendly solution to deliver the best of your products. Forget sudden temperature changes, reduce your workload and keep the highest hygienic standards: the new Back-Loading system is designed to ease the operations of butcher shops professionals by allowing the products loading process directly from inside the shop into the vending machine.

SSB-H2

BACK LOADER SLAVE 10

| TECHNICAL SPECIFICATIONS | SSB-H2 |
|---|------------------------|
| DIMENSIONS H x W x D (mm) | 1830 x 980 x 935 |
| WEIGHT (NET - Standard machine without options) | 295 Kg |
| NO. OF SELECTIONS PER SHELF | 10 |
| NO. OF SHELVES | Min. 4 / Max. 6 |
| NO. OF SELECTIONS | Max. 60 |
| PROTOCOL | Executive / MDB |
| COOLING SYSTEM CONTROL | Electronic |
| COOLING UNIT | HC2 |
| INTERNAL TEMPERATURE RANGE | +2°C up to +10°C |
| MAX. POWER CONSUMPTION | 460 W |
| POWER SUPPLY | 230 V - 50/60 Hz |
| CLIMATE CLASS | ST (+16°C up to +38°C) |
| ENERGY CLASS | D |
| ENERGY CONSUMPTION - kWh/annum | 1666 (Cat. 3) |