



Compact Vending, but Make it Cool!

SandenVendo's compact vending machines range expands its offer with UnoCool+(plus), the new, eco-friendly, and refrigerated tabletop solution created to allow more facilities to benefit from the service of a vending machine.

The tallest machine among the tabletop spiral models, yet always space-saving in a small footprint, UnoCool+ will accommodate products up to 230 mm in height in a 3-shelf configuration and 170 mm in a 4-shelf one.

Install it in pubs, office spaces, meeting rooms, sports facilities, and hotel receptions and load it with heat-sensitive products such as chocolate, protein drinks, or even cosmetics.

SUP

UnoCool+ Tabletop

TECHNICAL SPECIFICATIONS	SUP
DIMENSIONS H x W x D (mm)	980 x 590 x 620
WEIGHT (NET/GROSS - Standard machine without options)	80 Kg / 85 Kg
NO. OF SELECTIONS PER SHELF	4
NO. OF SHELVES	Standard 3 / Max. 4
NO. OF SELECTIONS	Max. 16
DISPLAY	TOUCH 7"
PROTOCOL	Executive / MDB
COOLING UNIT	Thermoelectric
COOLING SYSTEM CONTROL	Delta T=12°C vs. Ambient T
INTERNAL TEMPERATURE RANGE	10°C
MAX. POWER CONSUMPTION	120 W
POWER SUPPLY	220 V / 50 Hz
ENERGY CONSUMPTION - kWh/annum	1130



Compact Vending, but Make it Cool!

SandenVendo's compact vending machines range expands its offer with UnoCool+(plus), the new, eco-friendly, and refrigerated tabletop solution created to allow more facilities to benefit from the service of a vending machine.

The tallest machine among the tabletop spiral models, yet always space-saving in a small footprint, UnoCool+ will accommodate products up to 230 mm in height in a 3-shelf configuration and 170 mm in a 4-shelf one.

Install it in pubs, office spaces, meeting rooms, sports facilities, and hotel receptions and load it with heat-sensitive products such as chocolate, protein drinks, or even cosmetics.

SPS

UnoCool+ Tabletop Slave

TECHNICAL SPECIFICATIONS	SPS
DIMENSIONS H x W x D (mm)	980 x 475 x 620
WEIGHT (NET/GROSS - Standard machine without options)	61 Kg / 65 Kg
NO. OF SELECTIONS PER SHELF	4
NO. OF SHELVES	Standard 3 / Max. 4
NO. OF SELECTIONS	Max. 16
DISPLAY	TOUCH 7"
PROTOCOL	Executive / MDB
COOLING UNIT	Thermoelectric
COOLING SYSTEM CONTROL	Delta T=12°C vs. Ambient T
INTERNAL TEMPERATURE RANGE	10°C
MAX. POWER CONSUMPTION	120 W
POWER SUPPLY	220 V / 50 Hz
ENERGY CONSUMPTION - kWh/annum	1130