



DO IT SMART, BACK-LOAD IT

Load the vending machine directly from your shop.

The smart, easy and eco-friendly solution to deliver the best of your products. Forget sudden temperature changes, reduce your workload and keep the highest hygienic standards: the new Back-Loading system is designed to ease the operations of butcher shops professionals by allowing the products loading process directly from inside the shop into the vending machine.

SSB-H2

BACK LOADER SLAVE 10

TECHNICAL SPECIFICATIONS

SSB-H2

DIMENSIONS H x W x D (mm)	1830 x 980 x 935
WEIGHT (NET - Standard machine without options)	295 Kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Min. 4 / Max. 6
NO. OF SELECTIONS	Max. 60
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
COOLING UNIT	HC2
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
MAX. POWER CONSUMPTION	460 W
POWER SUPPLY	230 V - 50/60 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	D
ENERGY CONSUMPTION - kWh/annum	1666 (Cat. 3)

OPTIONAL

SPEEDY LIFT
BELT SYSTEM
ROTARY SYSTEM
KIT SANDWICH
KIT BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
SAFETY SLIDE COIN INSERT
SECURITY CASH BOX SYSTEM
WALL/FLOOR FIXING KIT
PAYMENT SYSTEM
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED CABINET COLOUR
SPECIAL LED FOR MEAT