



The ultimate outdoor vending solution

The new G-Snack Outdoor Slave is designed to provide extra flexibility to any outdoor vending business: a smart solution that can be connected to any existing master outdoor model to easily increase sales opportunities. Especially suitable for Extra Vending and merchandising items, G-Snack Outdoor Slave can accommodate a large array of edible products and beyond. Backed by SandenVendo's expertise in thermo-dynamics and cooling systems, G-Snack Outdoor Slave comes with a thermal-magnetic circuit breaker and a temperature controller specially designed to operate under severe weather conditions. IP34 waterproof certified, this model comes with a heated anti-condensation glass, a new anti-vandal design and a smart... [\(more at our website\)](#)

SSX OD / KSX OD

G-Snack Ten (X) Outdoor Slave

TECHNICAL SPECIFICATIONS

SSX OD / KSX OD

DIMENSIONS H x W x D (mm)	1900 x 1015 x 1010
WEIGHT (NET - Standard machine without options)	400 kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / max. 7
NO. OF SELECTIONS	max. 70
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	450 W
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1553 (Cat. 2) 1836 (Cat. 3) 1714 (Cat. 4)

OPTIONAL

SPEEDY LIFT
E-LABELING
ROTARY SYSTEM
BELT SYSTEM
KIT SANDWICH
KIT BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
WALL/FLOOR FIXING KIT
VARIOUS FITTING KITS



The ultimate outdoor vending solution

The new G-Snack Outdoor Slave is designed to provide extra flexibility to any outdoor vending business: a smart solution that can be connected to any existing master outdoor model to easily increase sales opportunities. Especially suitable for Extra Vending and merchandising items, G-Snack Outdoor Slave can accommodate a large array of edible products and beyond. Backed by SandenVendo's expertise in thermo-dynamics and cooling systems, G-Snack Outdoor Slave comes with a thermal-magnetic circuit breaker and a temperature controller specially designed to operate under severe weather conditions. IP34 waterproof certified, this model comes with a heated anti-condensation glass, a new anti-vandal design and a smart... [\(more at our website\)](#)

SS8 OD / KS8 OD

G-Snack Eight (VIII) Outdoor Slave

TECHNICAL SPECIFICATIONS

SS8 OD / KS8 OD

DIMENSIONS H x W x D (mm)	1900 x 870 x 1010
WEIGHT (NET - Standard machine without options)	300 Kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / max. 7
NO. OF SELECTIONS	Max. 56
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	450 W
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1232 (Cat. 2) 1619 (Cat. 3) 1414 (Cat. 4)

OPTIONAL

SPEEDY LIFT
E-LABELING
ROTARY SYSTEM
BELT SYSTEM
KIT SANDWICH
KIT BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
WALL/FLOOR FIXING KIT
VARIOUS FITTING KITS



The ultimate outdoor vending solution

The new G-Snack Outdoor Slave is designed to provide extra flexibility to any outdoor vending business: a smart solution that can be connected to any existing master outdoor model to easily increase sales opportunities. Especially suitable for Extra Vending and merchandising items, G-Snack Outdoor Slave can accommodate a large array of edible products and beyond. Backed by SandenVendo's expertise in thermo-dynamics and cooling systems, G-Snack Outdoor Slave comes with a thermal-magnetic circuit breaker and a temperature controller specially designed to operate under severe weather conditions. IP34 waterproof certified, this model comes with a heated anti-condensation glass, a new anti-vandal design and a smart... [\(more at our website\)](#)

SS6 OD / KS6 OD

G-Snack Six (VI) Outdoor Slave

TECHNICAL SPECIFICATIONS

SS6 OD / KS6 OD

DIMENSIONS H x W x D (mm)	1900 x 775 x 1010
WEIGHT (NET - Standard machine without options)	275 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / max. 7
NO. OF SELECTIONS	Max. 42
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	450 W
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1280 (Cat. 2) 1518 (Cat. 3) 1545 (Cat. 4)

OPTIONAL

SPEEDY LIFT
 ROTARY SYSTEM
 BELT SYSTEM
 KIT SANDWICH
 KIT BAGUETTE
 MOTORIZED LOCK DELIVERY EYELET
 SPECIAL CODED LOCK (RIELDA)
 WALL/FLOOR FIXING KIT
 VARIOUS FITTING KITS