



Iconic design meets the future of vending

The G-Snack Vendo Legend®² draws inspiration from the timeless silhouette of the original Vendo classics, reinterpreted through a rounded cabinet design, refined metal and aluminium accents, and distinctive vertical LED lighting. The eco-friendly refrigerant system is designed for dependable, long-term performance. Compact yet robust, the G-Snack Vendo Legend®² transforms every location into a modern smart retail point, while preserving the authentic Vendo charm that started it all.

SNX

G-Snack Vendo Legend® Ten (X) Slave

TECHNICAL SPECIFICATIONS	SNX
DIMENSIONS H x W x D (mm)	1830*x 1005 x 840
WEIGHT (NET - Standard machine without options)	290 Kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 70
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
CLIMATE CLASS	ST (+16°C up to +38°C)
COOLING UNIT	HCD - R290
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	350 W
ENERGY CLASS	TBC
ENERGY CONSUMPTION - kWh/annum	TBC

*With adjustable feet



Iconic design meets the future of vending

The G-Snack Vendo Legend® draws inspiration from the timeless silhouette of the original Vendo classics, reinterpreted through a rounded cabinet design, refined metal and aluminium accents, and distinctive vertical LED lighting. The eco-friendly refrigerant system is designed for dependable, long-term performance. Compact yet robust, the G-Snack Vendo Legend® transforms every location into a modern smart retail point, while preserving the authentic Vendo charm that started it all.

SN8

G-Snack Vendo Legend® Eight (VIII) Slave

TECHNICAL SPECIFICATIONS	SN8
DIMENSIONS H x W x D (mm)	1830*x 860 x 840
WEIGHT (NET - Standard machine without options)	240 Kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 56
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
CLIMATE CLASS	ST (+16°C up to +38°C)
COOLING UNIT	HCD - R290
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	350 W
ENERGY CLASS	TBC
ENERGY CONSUMPTION - kWh/annum	TBC

*With adjustable feet



Iconic design meets the future of vending

The G-Snack Vendo Legend®² draws inspiration from the timeless silhouette of the original Vendo classics, reinterpreted through a rounded cabinet design, refined metal and aluminium accents, and distinctive vertical LED lighting. The eco-friendly refrigerant system is designed for dependable, long-term performance. Compact yet robust, the G-Snack Vendo Legend®² transforms every location into a modern smart retail point, while preserving the authentic Vendo charm that started it all.

SN6

G-Snack Vendo Legend® Six (VI) Slave

TECHNICAL SPECIFICATIONS	SN6
DIMENSIONS H x W x D (mm)	1830*x 710 x 840
WEIGHT (NET - Standard machine without options)	220 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 42
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
CLIMATE CLASS	ST (+16°C up to +38°C)
COOLING UNIT	HCD - R290
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	350 W
ENERGY CLASS	TBC
ENERGY CONSUMPTION - kWh/annum	TBC

*With adjustable feet