

Tabletop Vending with Thermoelectric Cooling System

UnoCool is SandenVendo's tabletop snack dispenser designed to meet the demands of a clientele with limited space availability, who aspire to deliver temperature-sensitive products.

Load all your favorite drinks and snacks in this new eco-friendly device: UnoCool is our first vending solution powered by a Thermoelectric Cooler (TEC) that cools products up to a minimum of 8° C. Compact and space-saving, UnoCool is the perfect vending solution for venues such as pubs, office spaces, meeting rooms, sports facilities and hotel receptions



SUC

UnoCool Tabletop

TECHNICAL SPECIFICATIONS	SUC
DIMENSIONS H x W x D (mm)	800 x 590 x 620
WEIGHT (NET/GROSS - Standard machine without options)	70 Kg / 75 Kg
NO. OF SELECTIONS PER SHELF	4
NO. OF SHELVES	Standard 3 / Max. 4
NO. OF SELECTIONS	Max. 16
DISPLAY	TOUCH 7"
PROTOCOL	Executive / MDB
COOLING UNIT	Thermoelectric
COOLING SYSTEM CONTROL	Delta T=12°C vs. Ambient T
INTERNAL TEMPERATURE RANGE	10°C
MAX. POWER CONSUMPTION	120 W
POWER SUPPLY	220 V / 50 Hz
ENERGY CONSUMPTION - kWh/annum	841

Tabletop Vending with Thermoelectric Cooling System

UnoCool is SandenVendo's tabletop snack dispenser designed to meet the demands of a clientele with limited space availability, who aspire to deliver temperature-sensitive products.

Load all your favorite drinks and snacks in this new eco-friendly device: UnoCool is our first vending solution powered by a Thermoelectric Cooler (TEC) that cools products up to a minimum of 8° C. Compact and space-saving, UnoCool is the perfect vending solution for venues such as pubs, office spaces, meeting rooms, sports facilities and hotel receptions



SCS

UnoCool Tabletop Slave

TECHNICAL SPECIFICATIONS	SCS
DIMENSIONS H x W x D (mm)	800 x 475 x 620
WEIGHT (NET/GROSS - Standard machine without options)	59 Kg / 65 Kg
NO. OF SELECTIONS PER SHELF	4
NO. OF SHELVES	Standard 3 / Max. 4
NO. OF SELECTIONS	Max. 16
DISPLAY	TOUCH 7"
PROTOCOL	Executive / MDB
COOLING UNIT	Thermoelectric
COOLING SYSTEM CONTROL	Delta T=12°C vs. Ambient T
INTERNAL TEMPERATURE RANGE	10°C
MAX. POWER CONSUMPTION	120 W
POWER SUPPLY	220 V / 50 Hz
ENERGY CONSUMPTION - kWh/annum	841